

THE
AMERICAN JOURNAL

OF
SCIENCE AND ARTS.

CONDUCTED BY

BENJAMIN SILLIMAN, M. D. LL. D.

Prof. Chem., Min., &c. in Yale Coll.; Cor. Mem. Soc. Arts, Man. and Com; and
 For. Mem. Geol. Soc., London; Mem. Roy. Min. Soc., Dresden; Nat. Hist.
 Soc., Halle; Imp. Agric. Soc., Moscow; Hon. Mem. Lin. Soc., Paris;
 Nat. Hist. Soc. Belfast, Ire.; Phil. and Lit. Soc. Bristol, Eng.;
 Mem. of various Lit. and Scien. Soc. in America.

VOL. XXII.—JULY, 1832.

NEW HAVEN:

Published and Sold by HEZEKIAH HOWE & Co. and A. H. MALTBY.
 Baltimore, E. J. COALE & J. S. LITTELL.—Philadelphia, E. LITTELL and
 CAREY & HART.—New York, G. & C. & H. CARVILL.—Boston, HIL-
 LIARD, GRAY, LITTLE & WILKINS.

PRINTED BY HEZEKIAH HOWE & CO.

APPENDIX.

*On the Production of Currents and Sparks of Electricity from
 Magnetism; by Prof. J. HENRY.*

ALTHOUGH the discoveries of Oersted, Arago, Faraday, and others, have placed the intimate connection of electricity and magnetism in a most striking point of view, and although the theory of Ampere has referred all the phenomena of both these departments of science to the same general laws, yet until lately one thing remained to be proved by experiment, in order more fully to establish their identity; namely, the possibility of producing electrical effects from magnetism. It is well known that surprising magnetic results can readily be obtained from electricity, and at first sight it might be supposed that electrical effects could with equal facility be produced from magnetism; but such has not been found to be the case, for although the experiment has often been attempted, it has nearly as often failed.

It early occurred to me, that if galvanic magnets, on my plan, were substituted for ordinary magnets, in researches of this kind, more success might be expected. Besides their great power, these magnets possess other properties, which render them important instruments in the hands of the experimenter; their polarity can be instantaneously reversed, and their magnetism suddenly destroyed or called into full action, according as the occasion may require. With this view, I commenced, last August, the construction of a much larger galvanic magnet than, to my knowledge, had before been attempted, and also made preparations for a series of experiments with it on a large scale, in reference to the production of electricity from magnetism. I was, however, at that time, accidentally interrupted in the prosecution of these experiments, and have not been able since to resume them, until within the last few weeks, and then on a much smaller scale than was at first intended. In the mean time, it has been announced in the 117th number of the Library of Useful Knowledge, that the result so much sought after has at length been found by Mr. Faraday of the Royal Institution. It states that he has established the general fact, that when a piece of metal is moved in any direction, in front of a magnetic pole, electrical currents are developed in the metal, which pass in a direction at right angles to its own motion, and also that the application of this principle affords a complete and

satisfactory explanation of the phenomena of magnetic rotation. No detail is given of the experiments, and it is somewhat surprising that results so interesting, and which certainly form a new era in the history of electricity and magnetism, should not have been more fully described before this time in some of the English publications; the only mention I have found of them is the following short account from the Annals of Philosophy for April, under the head of Proceedings of the Royal Institution.

"Feb. 17.—Mr. Faraday gave an account of the first two parts of his researches in electricity; namely, Volta-electric induction and magneto-electric induction. If two wires, A and B, be placed side by side, but not in contact, and a Voltaic current be passed through A, there is instantly a current produced by induction in B, in the opposite direction. Although the principal current in A be continued, still the secondary current in B is not found to accompany it, for it ceases after the first moment, but when the principal current is stopped then there is a second current produced in B, in the opposite direction to that of the first produced by the inductive action, or in the same direction as that of the principal current.

"If a wire, connected at both extremities with a galvanometer, be coiled in the form of a helix around a magnet, no current of electricity takes place in it. This is an experiment which has been made by various persons hundreds of times, in the hope of evolving electricity from magnetism, and as in other cases in which the wishes of the experimenter and the facts are opposed to each other, has given rise to very conflicting conclusions. But if the magnet be withdrawn from or introduced into such a helix, a current of electricity is produced *whilst the magnet is in motion*, and is rendered evident by the deflection of the galvanometer. If a single wire be passed by a magnetic pole, a current of electricity is induced through it which can be rendered sensible."*

Before having any knowledge of the method given in the above account, I had succeeded in producing electrical effects in the following manner, which differs from that employed by Mr. Faraday, and which appears to me to develop some new and interesting facts. A piece of copper wire, about thirty feet long and covered with elastic varnish, was closely coiled around the middle of the soft iron armature of the galvanic magnet, described in Vol. XIX of the American Journal of Science, and which, when excited, will readily

* This extract will also be found on page 396 of this Journal.—Ed.

sustain between six hundred and seven hundred pounds. The wire was wound upon itself so as to occupy only about one inch of the length of the armature which is seven inches in all. The armature, thus furnished with the wire, was placed in its proper position across the ends of the galvanic magnet, and there fastened so that no motion could take place. The two projecting ends of the helix were dipped into two cups of mercury, and there connected with a distant galvanometer by means of two copper wires, each about forty feet long. This arrangement being completed, I stationed myself near the galvanometer and directed an assistant at a given word to immerse suddenly, in a vessel of dilute acid, the galvanic battery attached to the magnet. At the instant of immersion, the north end of the needle was deflected 30° to the west, indicating a current of electricity from the helix surrounding the armature. The effect, however, appeared only as a single impulse, for the needle, after a few oscillations, resumed its former undisturbed position in the magnetic meridian, although the galvanic action of the battery, and consequently the magnetic power was still continued. I was, however, much surprised to see the needle suddenly deflected from a state of rest to about 20° to the east, or in a contrary direction when the battery was withdrawn from the acid, and again deflected to the west when it was re-immersed. This operation was repeated many times in succession, and uniformly with the same result, the armature, the whole time, remaining immovably attached to the poles of the magnet, no motion being required to produce the effect, as it appeared to take place only in consequence of the instantaneous development of the magnetic action in one, and the sudden cessation of it in the other.

This experiment illustrates most strikingly the reciprocal action of the two principles of electricity and magnetism, if indeed it does not establish their absolute identity. In the first place, magnetism is developed in the soft iron of the galvanic magnet by the action of the currents of electricity from the battery, and secondly the armature, rendered magnetic by contact with the poles of the magnet, induces in its turn, currents of electricity in the helix which surrounds it; we have thus as it were electricity converted into magnetism and this magnetism again into electricity.

Another fact was observed which is somewhat interesting in as much as it serves, in some respects, to generalize the phenomena. After the battery had been withdrawn from the acid, and the needle of the galvanometer suffered to come to a state of rest after the resulting de-

flexion, it was again deflected in the same direction by partially detaching the armature from the poles of the magnet to which it continued to adhere from the action of the residual magnetism, and in this way, a series of deflections, all in the same direction, was produced by merely slipping off the armature, by degrees, until the contact was entirely broken. The following extract from the register of the experiments exhibits the relative deflections observed in one experiment of this kind.

At the instant of immersion of the battery,	deflec.	40° west.
“ “ “ “ “ “	“	18 east.
Armature partially detached,	“	7 east.
Armature entirely detached,	“	12 east.

The effect was reversed in another experiment, in which the needle was turned to the west in a series of deflections by dipping the battery but a small distance into the acid at first and afterwards immersing it by degrees.

From the foregoing facts, it appears that a current of electricity is produced, for an instant, in a helix of copper wire surrounding a piece of soft iron whenever magnetism is induced in the iron; and a current in an opposite direction when the magnetic action ceases; also that an instantaneous current in one or the other direction accompanies every change in the magnetic intensity of the iron.

Since reading the account before given of Mr. Faraday's method of producing electrical currents I have attempted to combine the effects of motion and induction; for this purpose a rod of soft iron ten inches long and one inch and a quarter in diameter, was attached to a common turning lathe, and surrounded with four helices of copper wire in such a manner that it could be suddenly and powerfully magnetized, while in rapid motion, by transmitting galvanic currents through three of the helices; the fourth being connected with the distant galvanometer was intended to transmit the current of induced electricity: all the helices were stationary while the iron rod revolved on its axis within them. From a number of trials in succession, first with the rod in one direction then in the opposite, and next in a state of rest, it was concluded that no perceptible effect was produced on the intensity of the *magneto-electric* current by a rotatory motion of the iron combined with its sudden magnetization.

The same apparatus however furnished the means of measuring separately the relative power of motion and induction in producing electrical currents. The iron rod was first magnetized by currents

through the helices attached to the battery and while in this state one of its ends was quickly introduced into the helix connected with the galvanometer; the deflection of the needle, in this case, was seven degrees. The end of the rod was next introduced into the same helix while in its natural state and then suddenly magnetized; the deflection, in this instance amounted to thirty degrees, shewing a great superiority in the method of induction.

The next attempt was to increase the *magneto-electric* effect while the magnetic power remained the same, and in this I was more successful. Two iron rods six inches long and one inch in diameter, were each surrounded by two helices and then placed perpendicularly on the face of the armature, and between it and the poles of the magnet so that each rod formed as it were a prolongation of the poles, and to these the armature adhered when the magnet was excited. With this arrangement, a current from one helix produced a deflection of thirty seven degrees; from two helices both on the same rod fifty two degrees, and from three fifty nine degrees: but when four helices were used, the deflection was only fifty five degrees, and when to these were added the helix of smaller wire around the armature, the deflection was no more than thirty degrees. This result may perhaps have been somewhat affected by the want of proper insulation in the several spires of the helices, it however establishes the fact that an increase in the electric current is produced by using at least two or three helices instead of one. The same principle was applied to another arrangement which seems to afford the maximum of electric development from a given magnetic power; in place of the two pieces of iron and the armature used in the last experiments, the poles of the magnet were connected by a single rod of iron, bent into the form of a horse-shoe, and its extremities filed perfectly flat so as to come in perfect contact with the faces of the poles: around the middle of the arch of this horse-shoe, two strands of copper wire were tightly coiled one over the other. A current from one of these helices deflected the needle one hundred degrees, and when both were used the needle was deflected with such force as to make a complete circuit. But the most surprising effect was produced when instead of passing the current through the long wires to the galvanometer, the opposite ends of the helices were held nearly in contact with each other, and the magnet suddenly excited; in this case a small but vivid spark was seen to pass between the ends of the wires and this effect was repeated as often as the state of intensity of the magnet was changed.

In these experiments the connection of the battery with the wires from the magnet was not formed by soldering, but by two cups of mercury which permitted the galvanic action on the magnet to be instantaneously suspended and the polarity to be changed and rechanged without removing the battery from the acid; a succession of vivid sparks was obtained by rapidly interrupting and forming the communication by means of one of these cups; but the greatest effect was produced when the magnetism was entirely destroyed and instantaneously reproduced by a change of polarity.

It appears from the May No. of the Annals of Philosophy, that I have been anticipated in this experiment of drawing sparks from the magnet by Mr. James D. Forbes of Edinburgh, who obtained a spark* on the 30th of March; my experiments being made during the last two weeks of June. A simple notification of his result is given, without any account of the experiment, which is reserved for a communication to the Royal Society of Edinburgh; my result is therefore entirely independent of his and was undoubtedly obtained by a different process.

I have made several other experiments in relation to the same subject, but which more important duties will not permit me to verify in time for this paper. I may however mention one fact which I have not seen noticed in any work and which appears to me to belong to the same class of phenomena as those before described: it is this; when a small battery is moderately excited by diluted acid and its poles, which must be terminated by cups of mercury, are connected by a copper wire not more than a foot in length, no spark is perceived when the connection is either formed or broken: but if a wire thirty or forty feet long be used, instead of the short wire, though no spark will be perceptible when the connection is made, yet when it is broken by drawing one end of the wire from its cup of mercury a vivid spark is produced. If the action of the battery be very intense, a spark will be given by the short wire; in this case it is only necessary to wait a few minutes until the action partially subsides and until no more sparks are given from the short wire; if the long wire be now substituted a spark will again be obtained. The effect appears somewhat increased by coiling the wire into a helix; it seems also to depend in some measure on the length and thickness of the wire; I can account for these phenomena only by supposing the long wire to become charged with electricity which by its reaction on itself projects a spark when the connection is broken.

* From a natural magnet.